

ULTIMA

5600 sxt Water Softener





This sophisticated system is easily programmed to match your family's water needs.

Five-cycle regeneration maximizes the system's efficiency. Demand-initiated regeneration saves you money on salt and water because the softener only regenerates when needed, based on your family's actual water usage. Plus, with internal by-pass, you'll always have continuous water during the backwash and regeneration cycles. External by-pass valve is also included for ease of service.

Our digital display makes programming simple. And there's no need to worry about power outages because the electronic system maintains your program settings.

The Ultima Water Softener: easy and versatile.

- The 1" flow-through valve meets NSF/ANSI 44 requirements. It's ideal for larger homes because it supplies more water with less pressure drop.
- The system's composite material is durable and corrosion-resistant.
- Cycles are fully adjustable so settings are customized for your needs.
- Designed with a minimum number of moving parts means easy maintenance.
- The sturdy polyethylene brine tank Holds up to 250 lbs. of salt. And the reliable brine safety valve incorporates built-in safeguards that prevent brine tank overflow.
- Highly efficient resin is designed to be long-lasting.
- Resin tank is NSF-certified and made from non-corrosive, reinforced fiberglass.

Residential Benefits

No Water Spots

Softer Clothes

Easier Rinsing

Less Detergent

No Scale Build-Up

Ultima Water Softener Specifications

Model#	Max. Capacity*	Tank Size	Max Drain Flow	Resin Cu. Ft.
56sxt024	24,000gr	8 x 44	1.5 gpm	0.75
56sxt032	32,000gr	9 x 48	2.0 gpm	1
56sxt040	40,000gr	10 x 44	2.4 gpm	1.25
56sxt048	48,000gr	10 x 54	2.4 gpm	1.5
56sxt064	64,000gr	12 x 52	3.5 gpm	2
56sxt080	80,000gr	13 x 54	4.0 gpm	2.5
56sxt096	96,000gr	14 x 65	5.0 gpm	3

* Based on 15 lbs. salt per cubic foot